



ATV-UTV EXPERT 4T 10W-40

Lubricant for 4 stroke ATV-UTV engines

Technosynthese®

TYPE OF USE

ATV – All Terrain Vehicle, UTV – Utility Terrain/Task Vehicle, quads...fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...
ATV-UTV, quads used for leisure and recreation.
Suitable for all type of gasoline fuels, leaded or unleaded, biofuels.

PERFORMANCE

STANDARDS API SM/SL/SJ
PERFORMANCES JASO MA

Technosynthese® engine oil, reinforced with synthetic base stocks which provide outstanding protection and oil film resistance.
Formula reinforced with anti-wear additives and improved shear resistance for improved oil film resistance at high temperatures.
The JASO MA performance guarantees the efficient friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.
Optimized Phosphorus and Sulfur contents for better operating conditions of catalytic converters required to meet latest emission regulation.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.870
Viscosity at 40°C (104°F)	ASTM D445	89.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	13.6 mm ² /s
Viscosity index	ASTM D2270	156
Pour point	ASTM D97	-32°C / -25.6°F
Flash point	ASTM D92	225°C / 437°F
TBN	ASTM D2896	7.6 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com